

MULTI-MIX® MEDIA

TYPE: MM-7000



MULTI-MIX® MEDIA

Circul-Aire manufactures a wide variety of unique MULTI-MIX® chemical filter media specially designed to remove an extensive range of contaminants from the air. Circul-Aire's MULTI-MIX® chemical filter media, used either individually or in combination, provide continuous purification of air containing corrosive, odorous, and toxic contaminants in both commercial and industrial environments.

Activated Carbon Impregnated with Phosphoric Acid

Circul-Aire's MM-7000 MULTI-MIX® media is a pelletized activated carbon impregnated with phosphoric acid for enhanced performance in removing basic gases, such as Ammonia (NH³), from air streams. Circul-Aire's MM-7000 MULTI-MIX® media is a chemisorbent manufactured from a unique bituminous coal substrate, with a low pressure drop and a high adsorptive removal capacity.

COMBINED PROPERTIES

NH ³ Capacity (minimum):	5.5 wt% (0.05 g NH ³ /cc)
Moisture:	15 wt%
Substrate Hardness:	95 wt%
Particle Diameter:	3 mm
Substrate CTC:	70 wt%
Substrate Surface Area:	1,250 m ² /g
Shape:	Pellet
Apparent Density:	0.64 g/cc (40 lb./ft ³)
Pressure Drop @ 50 fpm (0.25 m/s):	2.4 in. of water/ft. of bed

PERFORMANCE GUIDELINES

Circul-Aire's MM-7000 MULTI-MIX® media functions under the following conditions:

- Temperature: : -20°C to 51°C (-4°F to 125°F)
- Humidity: 10% to 95% RH
- Airflow: Ranging from less than 25 cfm(42.5 m³/hr.) to over 100,000 cfm (169,920 m³/hr.), with velocities from 60 fpm (0.305 m/s) to 500 fpm (2.54 m/s)

ADVANTAGES

- Nonhazardous
- Non-describing
- Unsupported of bacterial or fungal growth
- Media impregnated specifically to efficiently remove ammonia gas
- Compatible with other Circul-Aire MULTI-MIX® media
- Circul-Aire laboratory testing and analysis available to determine remaining service life, through Circul-Aire's TECH-CHEK™ Service

SAFETY PRECAUTIONS

- Wet activated carbon readily adsorbs atmospheric oxygen. Dangerously low oxygen levels may exist in closed vessels or poorly ventilated areas. **Workers should follow federal, provincial/state, and local safety guidelines for entering oxygen depleted areas**
- Keep away from heat
- Handle in a well-ventilated are
- Store in a cool, dry area, away from incompatible materials
- Always wear protective eye-wear and gloves when handling chemical media
- **Workers should follow federal, provincial/state, and local safety guidelines when disposing of MULTI-MIX® chemical media**
- Refer to Material Safety Data Sheet (M.S.D.S.) for further information

QUALITY CONTROL

Circul-Aire's MM-7000 MULTI-MIX® media undergoes the following quality control tests before shipment:

- Phosphoric Acid Content
- Moisture Content
- Size Distribution
- Bulk Density

PACKAGING

Circul-Aire's MM-7000 MULTI-MIX® media is available in 1-cu. ft. boxes and 6-cu. ft. or 20-cu. ft. super sacks. Unless otherwise specified, MM-7000 MULTI-MIX® media is supplied in 1-cu. ft. boxes.

TECH-CHEK™ SERVICE

Circul-Aire's TECH-CHEK™ Service is offered on an ongoing basis to all its clients at no additional charge. Samples of Circul-Aire's MULTI-MIX® chemical media, which are ideally taken quarterly from the client's filtration equipment, are sent to Circul-Aire's in-house, ISO-Certified laboratory, where the media is analyzed for Life Expended. Via a detailed report to the client, Circul-Aire's TECH-CHEK™ Service not only provides a precise maintenance schedule, but also ensures the highest performance of Circul-Aire's equipment at the most economical cost.

